## 2016 Civic coupe

NGINE	LX	EX-T	TOURING
2.0-litre, 16-valve, Port Injection, DOHC, i-VTEC® 4-cylinder .5-litre, 16-valve, Direct Injection, DOHC, turbocharged 4-cylinder	•	,	
Horsepower (@ rpm1	158 @ 6500	174 @ 6000	174 @ 6000
Torque (lbft. @ rpm) <sup>1</sup>	138 @ 4200	162 @ 1700-5500	162 @ 1700-5500
Displacement (cc)	1996	1498	1498
missions rating	Tier 3 Bin 125	Tier 3 Bin 125	Tier 3 Bin 125
ore and stroke (mm)	86 x 85.9	73 x 89.5	73 x 89.5
Compression ratio	10.8:1	10.6:1	10.6:1
orive-by-Wire Throttle System™ Co Assist™ system	•	•	•
Recommended fuel	Regular	Regular	Regular
DRIVETRAIN	LX	EX-T	TOURING
-speed manual transmission (MT)	•		
ontinuously variable transmission (CVT)	Available	•	•
CON mode button	•	•	•
ront-wheel drive	•	•	•
teering wheel-mounted paddle shifters		•	•
HASSIS	LX	EX-T	TOURING
" aluminum-alloy wheels (black finish) " aluminum-alloy wheels	•		
" aluminum-alloy wheels (aero design)		•	•
gile Handling Assist <sup>2</sup> (AHA)	•	•	•
ll-season tires	P215/55 R16 93H	P215/50 R17 91H	P215/50 R17 91H
apless fueling system	•	•	•
ariable Ratio Electric Power-Assisted Rack-and-Pinion Steering (EPS)	•	•	•
lectronic Parking Brake (EPB) with automatic brake hold	05.0/10.0	05 5/20 0	05 5/10 0
ront and rear stabilizer bars (mm) ndependent strut front suspension	25.0/16.0	25.5/16.0	25.5/16.0
ndependent multi-link rear suspension	•	•	
ower-assisted, ventilated front disc/solid rear disc brakes	•	•	•
traight Driving Assist	•	•	•
emporary spare tire	T125/80 D16 97M	T125/80 D16 97M	T125/80 D16 97N
CTIVE SAFETY	LX	EX-T	TOURING
-wheel Anti-lock Braking System² (ABS)	•	•	•
rake Assist	•	•	•
lectronic Brake-force Distribution (EBD)	•	•	•
rollision Mitigation Braking System™2 (CMBS®)	Honda Sensing™ model*	Honda Sensing™ model	•
orward Collision Warning (FCW) system² Iill Start Assist²	Honda Sensing™ model*	Honda Sensing™ model	•
ane Departure Warning (LDW) system <sup>2</sup>	Honda Sensing™ model*	Honda Sensing™ model	•
ED daytime running lights	•	•	•
load Departure Mitigation (RDM) system <sup>2</sup>	Honda Sensing™ model*	Honda Sensing™ model	•
ehicle Stability Assist² (VSA®) with Traction Control	•	•	•
Honda Sensing™ suite of safety and driver assist technologies are only available on CVT vehicles.			
ASSIVE SAFETY	LX	EX-T	TOURING
-point seat belts with front automatic tensioning system	•	•	•
lext-Generation Advanced Compatibility Engineering™ (ACE™) body structure ual-stage, multiple-threshold front airbags (SRS)	•	•	•
de curtain airbags with rollover sensor system	•	•	•
martvent™ side airbags	•	•	•
londaLink™ Assist Automatic Emergency Response System <sup>2,3,4</sup>	•	•	•
ower Anchors and Tethers for Children (LATCH)	•	•	•
RIVER ASSIST TECHNOLOGY	LX	EX-T	TOURING
daptive Cruise Control (ACC) <sup>2</sup> with Low-Speed Follow	Honda Sensing™ model*	Honda Sensing™ model	•
onda LaneWatch™ blind spot display²		•	•
ane Keeping Assist System (LKAS) <sup>2</sup>	Honda Sensing™ model*	Honda Sensing™ model	•
Honda Sensing™ suite of safety and driver assist technologies are only available on CVT vehicles.			
XTERIOR	LX	EX-T	TOURING
ody-coloured bumpers	•	•	•
ody-coloured door handles	•	•	Chrome
og lights		•	•
olding door mirrors ront splash guards		•	
eated power door mirrors including expanded view driver's mirror	Body-coloured	Body-coloured	Body-coloured w
		,	chrome accent
termittent windshield wipers	•		
ED front turn signal indicators			•
D headlights (High and low beam)			With auto-on/o
ED taillights	•	•	•
irror-integrated LED turn signal indicators ower moonroof with tilt feature		•	•
rojector-beam halogen headlights	With auto-on/off	With auto-on/off	•
ain-sensing windshield wipers			•
ear window defroster	•	•	•
hark fin antenna			•
shark fin antenna peed-sensing, variable intermittent windshield wipers aillight-integrated rear spoiler		•	•

COMFORT & CONVENIENCE	LX	EX-T	TOURING
12-volt power outlet	1	1	1
7" colour TFT centre meter display with Driver Information Interface	•	•	•
Acoustic windshield	•	•	•
Auto-dimming rearview mirror		Dual zona	• Dual zono
Automatic climate control with air-filtration system  Cargo area light	•	Dual-zone	Dual-zone
Display Audio System² with Honda Satellite-Linked Navigation System™2.5	·	•	•
with bilingual Voice Recognition			
Door pockets	•	•	•
Driver's and front passenger's vanity mirrors	•	Illuminated	Illuminated
Exterior temperature indicator	•	•	•
HandsFreeLink™-bilingual Bluetooth® wireless mobile phone interface <sup>2,3</sup>	•	•	•
Immobilizer theft-deterrent system	•	•	•
Maintenance Minder™ system	•	•	•
Map lights Multi-angle rearview camera <sup>2</sup>	With dynamic guidelines	With dynamic guidelines	With dynamic guideline
Multi-functional centre console storage	with dynamic guidelines	• with dynamic guidelines	• • • •
One-touch turn signals	•	•	•
Power windows with auto-up/down driver's and passenger's window	•	•	•
Power door locks	•	•	•
Proximity key entry system with pushbutton start		•	•
Remote engine starter		•	•
Remote entry system with electronic trunk release	•		
Security system	•	•	•
Steering wheel-mounted cruise control	•	•	•
Tilt and telescopic steering column	•	•	•
Walk-away door lock Wireless charging		•	•
SEATING & TRIM	LX	EX-T	TOURING
60/40 split fold-down rear seatback	•	•	•
Driver's seat with 6-way manual adjustment	•	•	•
Front passenger's seat with 4-way manual adjustment Floor mats	•	•	•
Heated front seats	•	•	•
Leather-trimmed seating surfaces	•	•	•
Leather-wrapped steering wheel		•	•
ENTERTAINMENT	LX	EX-T	TOURING
180-watt AM/FM audio system with MP3/Windows Media® Audio playback capability and 8 spe		LA I	TOOKING
450-watt AM/FM Premium audio system with MP3/Windows Media® Audio playback capability and a specific of the system with MP3/Windows Media® Audio playback	edicis	•	
capability and 10 speakers including subwoofer			
Apple CarPlay <sup>TM2,3</sup> / Android Auto <sup>TM2,3</sup>	•		
Bluetooth® Streaming Audio <sup>2,3</sup>	•	•	•
Display Audio System <sup>2</sup> with HondaLink™ <sup>2,3</sup>	•	•	Including Navigation <sup>2,5</sup>
HD Radio™ <sup>6</sup>			•
Illuminated steering wheel-mounted audio controls	With capacitive	With capacitive	With capacitive
0115 5 4141, 02	touch controls	touch controls	touch controls
Siri Eyes Free compatibility <sup>2,3</sup> SiriusXM <sup>™7</sup>	•	•	•
SMS text message <sup>2,3</sup> / E-mail function <sup>2,3</sup>			•
Speed-sensitive Volume Control (SVC)	•	•	
USB device connector <sup>3</sup>	2	2	2
Wi-Fi tethering <sup>3</sup>	•	•	•
FUEL ECONOMY <sup>®</sup> (L/100 KM)			
	IV	FV T	TOUDING
	LX	EX-T	TOURING
Continuously variable transmission (City/Hwy/Combined)	7.8 / 5.8 / 6.9	<b>EX-T</b> 7.5 / 5.6 / 6.7	<b>TOURING</b> 7.5 / 5.6 / 6.7
Manual transmission (City/Hwy/Combined)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7	7.5 / 5.6 / 6.7	7.5 / 5.6 / 6.7
Manual transmission (City/Hwy/Combined)  DIMENSIONS	7.8   5.8   6.9 8.9   6.1   7.7 LX	7.5 / 5.6 / 6.7 <b>EX-T</b>	7.5 / 5.6 / 6.7 <b>TOURING</b>
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7 LX 343	7.5 / 5.6 / 6.7 <b>EX-T</b> 343	7.5 / 5.6 / 6.7 <b>TOURING</b> 337
Manual transmission (City/Hwy/Combined)  DIMENSIONS	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7 LX 343 1251/1256	7.5 / 5.6 / 6.7 <b>EX-T</b> 343 NA/1313	7.5 / 5.6 / 6.7 <b>TOURING</b>
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L)  Curb weight - MT/CVT (kg)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7 <b>LX</b> 343 1251/1256 1257 (Honda Sensing™ model )	7.5 / 5.6 / 6.7 <b>EX-T</b> 343  NA/1313	7.5 / 5.6 / 6.7 <b>TOURING</b> 337 NA/1317
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L) Curb weight - MT/CVT (kg)  Fuel tank capacity (L)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7 <b>LX</b> 343 1251/1256 1257 (Honda Sensing™ model ) 46.9	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L)  Curb weight – MT/CVT (kg)  Fuel tank capacity (L)  Ground clearance – no-load/full-load (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7 <b>LX</b> 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L) Curb weight - MT/CVT (kg)  Fuel tank capacity (L) Ground clearance - no-load/full-load (mm) Headroom - front/rear (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7 LX 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105 970/879	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105  928/876
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L)  Curb weight – MT/CVT (kg)  Fuel tank capacity (L)  Ground clearance – no-load/full-load (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7 <b>LX</b> 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876  1395	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L)  Curb weight – MT/CVT (kg)  Fuel tank capacity (L)  Ground clearance – no-load/full-load (mm)  Headroom – front/rear (mm)  Height (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7 LX 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105 970/879 1395	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105  928/876  1395
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L) Curb weight – MT/CVT (kg)  Fuel tank capacity (L) Ground clearance – no-load/full-load (mm) Headroom – front/rear (mm) Height (mm) Hip room – front/rear (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7  LX 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105 970/879 1395 1374/1223	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876  1395  1374/1223	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105  928/876  1395  1374/1223
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L)  Curb weight – MT/CVT (kg)  Fuel tank capacity (L)  Ground clearance – no-load/full-load (mm)  Headroom – front/rear (mm)  Height (mm)  Hip room – front/rear (mm)  Legroom – front/rear (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7  LX 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105 970/879 1395 1374/1223 1074/912	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876  1395  1374/1223  1074/912	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105  928/876  1395  1374/1223  1074/912
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L) Curb weight – MT/CVT (kg)  Fuel tank capacity (L) Ground clearance – no-load/full-load (mm) Headroom – front/rear (mm) Height (mm) Hip room – front/rear (mm) Legroom – front/rear (mm) Length (mm) Passenger volume (L) Shoulder room – front/rear (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7  LX 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105 970/879 1395 1374/1223 1074/912 4492 2577 1446/1336	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876  1395  1374/1223  1074/912  4492	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105  928/876  1395  1374/1223  1074/912  4492  2509  1446/1336
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L)  Curb weight – MT/CVT (kg)  Fuel tank capacity (L)  Ground clearance – no-load/full-load (mm)  Headroom – front/rear (mm)  Height (mm)  Hip room – front/rear (mm)  Legroom – front/rear (mm)  Length (mm)  Passenger volume (L)  Shoulder room – front/rear (mm)  Track – front/rear (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7  LX 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105 970/879 1395 1374/1223 1074/912 4492 2577 1446/1336 1547/1563	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876  1395  1374/1223  1074/912  4492  2509  1446/1336  1547/1563	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105  928/876  1395  1374/1223  1074/912  4492  2509  1446/1336  1547/1563
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L) Curb weight - MT/CVT (kg)  Fuel tank capacity (L) Ground clearance - no-load/full-load (mm) Headroom - front/rear (mm) Height (mm)  Hip room - front/rear (mm) Legroom - front/rear (mm) Legroom - front/rear (mm) Track - front/rear (mm) Turning radius (m) (curb-to-curb)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7  LX 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105 970/879 1395 1374/1223 1074/912 4492 2577 1446/1336 1547/1563 5.4	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876  1395  1374/1223  1074/912  4492  2509  1446/1336  1547/1563  5.4	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105  928/876  1395  1374/1223  1074/912  4492  2509  1446/1336  1547/1563  5.4
Manual transmission (City/Hwy/Combined)  DIMENSIONS  Cargo volume (L)  Curb weight - MT/CVT (kg)  Fuel tank capacity (L)  Ground clearance - no-load/full-load (mm)  Headroom - front/rear (mm)  Height (mm)  Hip room - front/rear (mm)  Legroom - front/rear (mm)  Length (mm)  Passenger volume (L)  Shoulder room - front/rear (mm)  Track - front/rear (mm)	7.8 / 5.8 / 6.9 8.9 / 6.1 / 7.7  LX 343 1251/1256 1257 (Honda Sensing™ model ) 46.9 125/105 970/879 1395 1374/1223 1074/912 4492 2577 1446/1336 1547/1563	7.5 / 5.6 / 6.7  EX-T  343  NA/1313  46.9  125/105  928/876  1395  1374/1223  1074/912  4492  2509  1446/1336  1547/1563	7.5 / 5.6 / 6.7  TOURING  337  NA/1317  46.9  125/105  928/876  1395  1374/1223  1074/912  4492  2509  1446/1336  1547/1563

Horsepower and torque calculations reflect SAE net, Rev. 08/04, SAE JI349 procedures.
 None of the features we describe are intended to replace the driver's responsibility to exercise due care while driving. Drivers should not use handheld devices or operate certain vehicle features unless it is safe and legal to do so. Some features have technological limitations. For additional feature information, limitations and restrictions, please visit www.honda.ca/disclaimers and refer to the vehicle's Owner's Manual.
 Only compatible with certain devices and operating systems. Cellular data and/or voice charges may apply, including roaming charges and/or other amounts charged by your wireless carrier.
 Operation requires wireless mobile phone to be paired with the vehicle. Operation is dependent upon cellular data and/or voice connection availability and GPS satellite signal reception.
 Map database covers major metropolitan areas in Canada and the 48 contiguous U.S. states.
 Coverage varies by market.
 Only available in certain areas. Includes a no-charge trial of three months.
 Estimated fuel economy based on Government of Canada's 5-cycle testing method. Your actual fuel consumption will vary based on driving habits and other factors – use for comparison only. For more information on 5-cycle testing, visit http://vehicles.nrcan.gc.ca