

**HS622TC/TCS**


Engine power is transmitted to the track drive via a 2-speed plus reverse gearbox which eliminates maintenance and slippage. The auger is driven through a multi-disc dry clutch mechanism which eliminates periodic drive belt adjustment or replacement.

The HS622 models also feature Honda Track Drive – pliable rubber tracks with cleats support the snowblower's weight to give superior traction and extra grip on steep driveways and steps.

120 volt AC electric start provides an additional level of convenience on the HS622TCS.

### Features

- Dual-stage, track drive, clears a 22 in/56 cm width
- Honda GX160K1, OHV, 4-stroke engine
- 2-speed forward transmission plus reverse
- 3-way adjustable auger housing height
- 14 m/46 ft. max. discharge; up to 37 metric tons (41 tons)/hr.
- 120 volt AC electric start (HS622TCS model only)
- Work light (HS622TCS model only)

### Specifications

Discharge Type	Dual stage
Axle Type	Track drive
Drive Type	Gear mesh transmission
Speeds	2 forward / 1 reverse
Maximum Ground Speed	1 : 11.4 m/min. (37.4 ft./min)
Clearing Width	55.0 cm (21.7 in)
Intake Housing Height	42.0 cm (16.5 in)
Auger Diameter	30.5 cm (12.0 in)
Auger Type	Steel
Auger Drive	Dry, multi-disc clutch
Auger Height Adjustment	3 position adjuster
Chute Rotation	Manual lever
Chute Turning Radius	195°
Deflection Control	Manual lever
Chute Material	Steel
Maximum Throw Distance *	14 m (46 ft)
Clearing Snow Volume Capacity (Approximate)*	up to 37 metric tons (41 tons/hr)

### Engine

Engine Type	4-stroke, OHV, single cylinder
Honda Engine Model	GX160K1
Displacement	163 cc (10.0 CID)
Ignition System	Transistorized
Recoil Starter	Standard
Electric Starter	Standard 120 VAC type (HS622TCS)
Lubrication System	Forced splash
Oil Capacity	0.60 Litre (21.1 fl. Imp. oz)
Recommended Fuel	Regular unleaded gasoline (87 Octane)
Fuel Capacity	3.50 Litres (0.77 Imp. gal)
Operational Time per Tankful **	3.5 hours

### Dimensions

Wheel/Tire Size	N/A
Overall Length	150.0 cm (59.1 in)
Overall Width	55.0 cm (21.7 in)
Overall Height	112.5 cm (44.3 in)
Dry Weight	68.0 kg (149.9 lb) HS622TC 77.0 kg (169.8 lb) HS622TCS

### Accessories

Lighting Coil	No/Std.
Worklight	No/Std.

### Warranty

Term	2 year (non-commercial)
------	-------------------------